
World Housing Encyclopedia

*an Encyclopedia of Housing Construction in
Seismically Active Areas of the World*



an initiative of
Earthquake Engineering Research Institute (EERI) and
International Association for Earthquake Engineering (IAEE)

HOUSING REPORT

Confined brick masonry building with concrete tie columns and beams

Report #	27
Report Date	06-05-2002
Country	IRAN
Housing Type	Confined Masonry Building
Housing Sub-Type	Confined Masonry Building with Concrete blocks, tie-columns and beams
Author(s)	Behrokh H. Hashemi, Faramarz Alemi, Mohsen G. Ashtiany
Reviewer(s)	Farzad Naeim

Important

This encyclopedia contains information contributed by various earthquake engineering professionals around the world. All opinions, findings, conclusions & recommendations expressed herein are those of the various participants, and do not necessarily reflect the views of the Earthquake Engineering Research Institute, the International Association for Earthquake Engineering, the Engineering Information Foundation, John A. Martin & Associates, Inc. or the participants' organizations.

Summary

This is a typical confined brick masonry housing construction common in rural areas of Iran. This building type is often used as a single-family house. Brick masonry shear walls confined with concrete tie columns and beams provide earthquake resistance in both directions. This

building type is expected to have good seismic performance.

1. General Information

Buildings of this construction type can be found in rural areas of Iran. The percentage of this housing type in those regions is almost 10%. This type of housing construction is commonly found in rural areas. This construction type has been in practice for less than 50 years.

Currently, this type of construction is being built. .




Figure 1: Typical Building




Figure 2A: Key Load-Bearing Elements




Figure 2B: Key Load-Bearing Elements

2. Architectural Aspects

2.1 Siting

These buildings are typically found in flat, sloped and hilly terrain. They do not share common walls with adjacent buildings. This value of 5 meters is average distance. Buildings of this type in some places are located close together and in other places are scattered. When separated from adjacent buildings, the typical distance from a neighboring building is 5 meters.

2.2 Building Configuration

The typical shape of a building plan for this housing type is rectangular. To view outside the building, typically a window opening is built in external walls. These windows almost take 40% of the external walls areas. The other wall has one or two doors. The door sizes are typically 90 X 210 (cm). The overall window and door areas are about 25% of the overall wall surface area.

2.3 Functional Planning

The main function of this building typology is single-family house. In a typical building of this type, there are no elevators and 1-2 fire-protected exit staircases. Building of this type can have as the one main entry so the two doors.

2.4 Modification to Building

This type of construction does not have many modifications.

3. Structural Details

3.1 Structural System

Material	Type of Load-Bearing Structure	#	Subtypes	Most appropriate type
Masonry	Stone Masonry Walls	1	Rubble stone (field stone) in mud/lime mortar or without mortar (usually w with timber roof)	<input type="checkbox"/>
		2	Dressed stone masonry (in lime/cement mortar)	<input type="checkbox"/>
	Adobe/ Earthen Walls	3	Mud walls	<input type="checkbox"/>
		4	Mud walls with horizontal wood elements	<input type="checkbox"/>
		5	Adobe block walls	<input type="checkbox"/>
		6	Rammed earth/Pise construction	<input type="checkbox"/>
	Unreinforced masonry walls	7	Brick masonry in mud/lime mortar	<input type="checkbox"/>
		8	Brick masonry in mud/lime mortar with vertical posts	<input type="checkbox"/>
		9	Brick masonry in lime/cement mortar	<input type="checkbox"/>
		10	Concrete block masonry in cement mortar	<input type="checkbox"/>
	Confined masonry	11	Clay brick/tile masonry, with wooden posts and beams	<input type="checkbox"/>
		12	Clay brick masonry, with concrete posts/tie columns and beams	<input type="checkbox"/>
		13	Concrete blocks, tie columns and beams	<input checked="" type="checkbox"/>
	Reinforced masonry	14	Stone masonry in cement mortar	<input type="checkbox"/>
		15	Clay brick masonry in cement mortar	<input type="checkbox"/>
		16	Concrete block masonry in cement mortar	<input type="checkbox"/>
Structural concrete	Moment resisting frame	17	Flat slab structure	<input type="checkbox"/>
		18	Designed for gravity loads only, with URM infill walls	<input type="checkbox"/>
		19	Designed for seismic effects, with URM infill walls	<input type="checkbox"/>
		20	Designed for seismic effects, with structural infill walls	<input type="checkbox"/>
		21	Dual system – Frame with shear wall	<input type="checkbox"/>
	Structural wall	22	Moment frame with in-situ shear walls	<input type="checkbox"/>
		23	Moment frame with precast shear walls	<input type="checkbox"/>
	Precast concrete	24	Moment frame	<input type="checkbox"/>
		25	Prestressed moment frame with shear walls	<input type="checkbox"/>
		26	Large panel precast walls	<input type="checkbox"/>
		27	Shear wall structure with walls cast-in-situ	<input type="checkbox"/>
		28	Shear wall structure with precast wall panel structure	<input type="checkbox"/>
Moment-resisting frame	29	With brick masonry partitions	<input type="checkbox"/>	
	30	With cast in-situ concrete walls	<input type="checkbox"/>	
	31	With lightweight partitions	<input type="checkbox"/>	

Steel	Braced frame	32	Concentric connections in all panels	<input type="checkbox"/>
		33	Eccentric connections in a few panels	<input type="checkbox"/>
	Structural wall	34	Bolted plate	<input type="checkbox"/>
		35	Welded plate	<input type="checkbox"/>
Timber	Load-bearing timber frame	36	Thatch	<input type="checkbox"/>
		37	Walls with bamboo/reed mesh and post (Wattle and Daub)	<input type="checkbox"/>
		38	Masonry with horizontal beams/planks at intermediate levels	<input type="checkbox"/>
		39	Post and beam frame (no special connections)	<input type="checkbox"/>
		40	Wood frame (with special connections)	<input type="checkbox"/>
		41	Stud-wall frame with plywood/gypsum board sheathing	<input type="checkbox"/>
Other	Seismic protection systems	42	Wooden panel walls	<input type="checkbox"/>
		43	Building protected with base-isolation systems	<input type="checkbox"/>
	Hybrid systems	44	Building protected with seismic dampers	<input type="checkbox"/>
		45	Other (described below)	<input type="checkbox"/>

3.2 Gravity Load-Resisting System

The vertical load-resisting system is confined masonry wall system. Gravity loads sustain by bearing masonry brick walls.

3.3 Lateral Load-Resisting System

The lateral load-resisting system is confined masonry wall system. In both directions of the buildings lateral load-resisting system are provided by masonry brick shear walls which are confined with concrete tie column and beams.

3.4 Building Dimensions

The typical plan dimensions of these buildings are: lengths between 5 and 5 meters, and widths between 9 and 9 meters. The building has 4 to 6 storey(s). The typical span of the roofing/flooring system is 2.5 meters. Typical Span: Span may be 3.0 m. The typical storey height in such buildings is 3 meters. The typical structural wall density is up to 20 %. Total wall area/plan area (for each floor) 0.2.

3.5 Floor and Roof System

Material	Description of floor/roof system	Most appropriate floor	Most appropriate roof
Masonry	Vaulted	<input type="checkbox"/>	<input type="checkbox"/>
	Composite system of concrete joists and masonry panels	<input type="checkbox"/>	<input type="checkbox"/>
Structural concrete	Solid slabs (cast-in-place)	<input type="checkbox"/>	<input type="checkbox"/>
	Waffle slabs (cast-in-place)	<input type="checkbox"/>	<input type="checkbox"/>
	Flat slabs (cast-in-place)	<input type="checkbox"/>	<input type="checkbox"/>
	Precast joist system	<input type="checkbox"/>	<input type="checkbox"/>
	Hollow core slab (precast)	<input type="checkbox"/>	<input type="checkbox"/>

	Solid slabs (precast)	<input type="checkbox"/>	<input type="checkbox"/>
	Beams and planks (precast) with concrete topping (cast-in-situ)	<input type="checkbox"/>	<input type="checkbox"/>
	Slabs (post-tensioned)	<input type="checkbox"/>	<input type="checkbox"/>
Steel	Composite steel deck with concrete slab (cast-in-situ)	<input type="checkbox"/>	<input type="checkbox"/>
Timber	Rammed earth with ballast and concrete or plaster finishing	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams with ballast and concrete or plaster finishing	<input type="checkbox"/>	<input type="checkbox"/>
	Thatched roof supported on wood purlins	<input type="checkbox"/>	<input type="checkbox"/>
	Wood shingle roof	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams that support clay tiles	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams supporting natural stones slates	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams that support slate, metal, asbestos-cement or plastic corrugated sheets or tiles	<input type="checkbox"/>	<input type="checkbox"/>
	Wood plank, plywood or manufactured wood panels on joists supported by beams or walls	<input type="checkbox"/>	<input type="checkbox"/>
Other	Described below	<input type="checkbox"/>	<input checked="" type="checkbox"/>

The floor/ and roof are considered to be a rigid diaphragm.

3.6 Foundation

Type	Description	Most appropriate type
Shallow foundation	Wall or column embedded in soil, without footing	<input type="checkbox"/>
	Rubble stone, fieldstone isolated footing	<input type="checkbox"/>
	Rubble stone, fieldstone strip footing	<input type="checkbox"/>
	Reinforced-concrete isolated footing	<input type="checkbox"/>
	Reinforced-concrete strip footing	<input checked="" type="checkbox"/>
	Mat foundation	<input type="checkbox"/>
	No foundation	<input type="checkbox"/>
Deep foundation	Reinforced-concrete bearing piles	<input type="checkbox"/>
	Reinforced-concrete skin friction piles	<input type="checkbox"/>
	Steel bearing piles	<input type="checkbox"/>
	Steel skin friction piles	<input type="checkbox"/>
	Wood piles	<input type="checkbox"/>
	Cast-in-place concrete piers	<input type="checkbox"/>
	Caissons	<input type="checkbox"/>
Other	Described below	<input type="checkbox"/>




Figure 3: Critical Structural Details: Concrete tie column




Figure 4A: An Illustration of Key Seismic Deficiencies: lack of Connection Between Wooden Beam and Concrete Tie Beam and Poor Quality of Materials




Figure 4B: Wall cross-section showing a concrete tie beam ad roof-to-wall connection




Figure 4C: Wall side view showing a concrete tie beam and roof-to-wall connection

4. Socio-Economic Aspects

4.1 Number of Housing Units and Inhabitants

Each building typically has 1 housing unit(s). 1 units in each building. The number of inhabitants in a building during the day or business hours is less than 5. The number of inhabitants during the evening and night is less than 5.

4.2 Patterns of Occupancy

One family usually occupies each house.

4.3 Economic Level of Inhabitants

Income class	Most appropriate type
a) very low -income class (very poor)	<input checked="" type="checkbox"/>
b) low -income class (poor)	<input type="checkbox"/>
c) middle-income class	<input type="checkbox"/>
d) high-income class (rich)	<input type="checkbox"/>

Economic Level: For Poor Class the Housing Price Unit is 5000 and the Annual Income is 1000.

Ratio of housing unit price to annual income	Most appropriate type
5:1 or worse	<input checked="" type="checkbox"/>
4:1	<input type="checkbox"/>
3:1	<input type="checkbox"/>
1:1 or better	<input type="checkbox"/>

What is a typical source of

financing for buildings of this type?	Most appropriate type
Owner financed	<input checked="" type="checkbox"/>
Personal savings	<input checked="" type="checkbox"/>
Informal network: friends and relatives	<input type="checkbox"/>
Small lending institutions / micro-finance institutions	<input type="checkbox"/>
Commercial banks/mortgages	<input checked="" type="checkbox"/>
Employers	<input type="checkbox"/>
Investment pools	<input type="checkbox"/>
Government-owned housing	<input type="checkbox"/>
Combination (explain below)	<input type="checkbox"/>
other (explain below)	<input type="checkbox"/>

In each housing unit, there are 1 bathroom(s) without toilet(s), 1 toilet(s) only and no bathroom(s) including toilet(s).

4.4 Ownership

The type of ownership or occupancy is outright ownership and ownership with debt (mortgage or other).

Type of ownership or occupancy?	Most appropriate type
Renting	<input type="checkbox"/>
outright ownership	<input checked="" type="checkbox"/>
Ownership with debt (mortgage or other)	<input checked="" type="checkbox"/>
Individual ownership	<input type="checkbox"/>
Ownership by a group or pool of persons	<input type="checkbox"/>
Long-term lease	<input type="checkbox"/>
other (explain below)	<input type="checkbox"/>

5. Seismic Vulnerability

5.1 Structural and Architectural Features

Structural/ Architectural Feature	Statement	Most appropriate type		
		Yes	No	N/A
Lateral load path	The structure contains a complete load path for seismic force effects from any horizontal direction that serves to transfer inertial forces from the building to the foundation.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Building Configuration	The building is regular with regards to both the plan and the elevation.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Roof construction	The roof diaphragm is considered to be rigid and it is expected that the roof structure will maintain its integrity, i.e. shape and form, during an earthquake of intensity expected in this area.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Floor construction	The floor diaphragm(s) are considered to be rigid and it is expected that the floor structure(s) will maintain its integrity during an earthquake of intensity expected in this area.	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Foundation performance	There is no evidence of excessive foundation movement (e.g. settlement) that would affect the integrity or performance of the structure in an earthquake.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wall and frame structures-redundancy	The number of lines of walls or frames in each principal direction is greater than or equal to 2.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wall proportions	Height-to-thickness ratio of the shear walls at each floor level is: Less than 25 (concrete walls); Less than 30 (reinforced masonry walls); Less than 13 (unreinforced masonry walls);	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Foundation-wall connection	Vertical load-bearing elements (columns, walls) are attached to the foundations; concrete columns and walls are doweled into the foundation.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wall-roof connections	Exterior walls are anchored for out-of-plane seismic effects at each diaphragm level with metal anchors or straps	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wall openings	The total width of door and window openings in a wall is: For brick masonry construction in cement mortar : less than 1/2 of the distance between the adjacent cross walls; For adobe masonry, stone masonry and brick masonry in mud mortar: less than 1/3 of the distance between the adjacent cross walls; For precast concrete wall structures: less than 3/4 of the length of a perimeter wall.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Quality of building materials	Quality of building materials is considered to be adequate per the requirements of national codes and standards (an estimate).	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Quality of workmanship	Quality of workmanship (based on visual inspection of few typical buildings) is considered to be good (per local construction standards).	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Maintenance	Buildings of this type are generally well maintained and there are no visible signs of deterioration of building elements (concrete, steel, timber)	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Additional Comments				

5.2 Seismic Features

Structural Element	Seismic Deficiency	Earthquake Resilient Features	Earthquake Damage Patterns
Wall	Unequal stiffness distribution.		
Frame (columns, beams)	Poor quality of workmanship and materials.		
Roof and floors	Lack of proper connection between roof and masonry shear walls They are not perfectly rigid diaphragm.		

5.3 Overall Seismic Vulnerability Rating

The overall rating of the seismic vulnerability of the housing type is *C: MEDIUM VULNERABILITY (i.e., moderate*

seismic performance), the lower bound (i.e., the worst possible) is B: MEDIUM-HIGH VULNERABILITY (i.e., poor seismic performance), and the upper bound (i.e., the best possible) is D: MEDIUM-LOW VULNERABILITY (i.e., good seismic performance).

Vulnerability	high	medium-high	medium	medium-low	low	very low
	very poor	poor	moderate	good	very good	excellent
Vulnerability Class	A	B	C	D	E	F
	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

5.4 History of Past Earthquakes

Date	Epicenter, region	Magnitude	Max. Intensity
1990	Manjil	7.6	IX



Figure 5: Damage caused by the absence of concrete posts (1990 Manjil earthquake)




Figure 6A: Illustration of Seismic Strengthening Techniques



Figure 6B: Damage due to large opening, absence of masonry shear wall and short column behavior in concrete post (1990 Manjil earthquake)



Figure 6C: Damage in the wall panel (1990 Manjil earthquake)



Figure 6D: Collapse due to heavy roof (1990 Manjil earthquake)

6. Construction

6.1 Building Materials

Structural element	Building material	Characteristic strength	Mix proportions/ dimensions	Comments
Walls	Clay brick masonry.	150 Kg/cm ² 10 Kg/cm ² .	1:6 / 55 X 110 X 220 (mm).	
Foundation	Concrete.	210 kg/cm ² .	1:2:4	
Frames (beams & columns)	Steel bars.	3000 kg/cm ² .		
Roof and floor(s)	Wood.			

6.2 Builder

It is typically built by developers and the builders does not necessary live in this building type.

6.3 Construction Process, Problems and Phasing

Typically developers build these types of constructions. Process starts with the foundations and then bearing walls. Process continues by adding the concrete tie columns and then tie beams then placing of wood beams and finally putting the finishing on the hole building. The construction of this type of housing takes place incrementally over time. Typically, the building is originally designed for its final constructed size.

6.4 Design and Construction Expertise

As far as the design concern, engineers do their job properly. But the main problem is the construction of this type of buildings in rural areas, due to lack of skilled worker. For design of building, engineers and architectures are both involved. However, during the construction process they do not spend any time to visit the site.

6.5 Building Codes and Standards

This construction type is addressed by the codes/standards of the country. The first official issue about this type of building was in 1987. The Iranian Code of Practice for Seismic Resistant Design of Buildings (Standard 2800) addressed this type of construction. Iranian Code of Practice for Seismic Resistant Design of Building, 1st Edition-1987 and 2nd Edition-1999 Iranian National Building Code, Part: 8, Reinforced and unreinforced masonry buildings. The year the first code/standard addressing this type of construction issued was 1987. Iranian Code of Practice for Seismic Resistant Design of Building, 1st Edition- 1987 and 2nd Edition-1999. The most recent code/standard addressing this construction type issued was 1999. The first official issue about this type of building was in 1987. The Iranian Code of Practice for Seismic Resistant Design of Buildings (Standard 2800) addressed this type of construction. Iranian Code of Practice for Seismic Resistant Design of Building, 1st Edition- 1987 and 2nd Edition-1999 Iranian National Building Code, Part: 8, Reinforced and unreinforced masonry buildings Year the first code/standard addressing this type of construction issued: 1987 National building code, material codes and seismic codes/standards: Iranian Code of Practice for Seismic Resistant Design of Building, 1st Edition- 1987 and 2nd Edition-1999 When was the most recent code/standard addressing this construction type issued? 1999.

The building department of municipalities approves the design and holds the designer responsible for the projects. For those constructions, which are supported by government's fund, there is a proper control during construction. But for the others, there is not any control.

6.6 Building Permits and Development Control Rules

This type of construction is an engineered, and not authorized as per development control rules. Building permits are required to build this housing type.

6.7 Building Maintenance

Typically, the building of this housing type is maintained by Owner(s) and Tenant(s).

6.8 Construction Economics

A unit construction may cost 500,000 Rials/m² (250 \$US/m²). For a typical one story building needs about 30 to 40 days to complete the load bearing structure.

7. Insurance

Earthquake insurance for this construction type is typically unavailable. For seismically strengthened existing

buildings or new buildings incorporating seismically resilient features, an insurance premium discount or more complete coverage is unavailable.

8. Strengthening

8.1 Description of Seismic Strengthening Provisions

Strengthening of Existing Construction :

Seismic Deficiency	Description of Seismic Strengthening provisions used
Shear wall	Add new shear wall
Tie beams	Increasing the size of the existing tie beams and adding new tie beams for added new walls
Roof	Proper connections of the wood beams to the tie beams

Strengthening of New Construction :

Seismic Deficiency	Description of Seismic Strengthening provisions used
Shear wall	
Tie beams	
Roof	Proper connections of the wood beams to the tie beams.

Seismic strengthening techniques are illustrated in Figures 7A, 7B, and 7C.

8.2 Seismic Strengthening Adopted

Has seismic strengthening described in the above table been performed in design and construction practice, and if so, to what extent?

No.

8.3 Construction and Performance of Seismic Strengthening




Figure 7A: Seismic Strengthening: Tying the wooden beam to the concrete

Reference(s)

1. A Simple Pictorial Guideline for Constructing Earthquake Resistant Adobe Building In Different Rural Areas
Hosseini Hashemi,B. and Alemi,F.
to be published in Farsi
2. Manjil-Rudbar Earthquake of June 20,90 Reconnaissance Report
IIEES Publication No. 70-91-1, Tehran, Iran 1991
3. Iranian Code of Practice for Seismic Resistant Design of Building, 1st Edition- 1987 and 2nd Edition-1999
Building and Housing Research Center, BHRC-PN S 253, Tehran, Iran
4. Iranian National Building Code - Part 8: Reinforced and unreinforced masonry buildings
Ministry of Housing and Urban Development, Tehran, Iran

Author(s)

1. Behrokh H. Hashemi
Assistant Professor, IIEES
No. 27 Arghavan St. Dibaji Farmanieh, Tehran 19531, IRAN
Email:behrokh@iiees.ac.ir FAX: (98-21) 229-9479
2. Faramarz Alemi, IIEES
No. 27 Arghavan Street Dibaji Farmanieh, Tehran 19531, IRAN
Email:f-alemi@dena.iiees.ac.ir FAX: (98-21) 229-9479
3. Mohsen G. Ashtiany
Professor/President, IIEES
No. 27 Arghavan Street Dibaji Farmanieh, Tehran 19531, IRAN
Email:ashtiany@dena.iiees.ac.ir FAX: (98-21) 229-9479

Reviewer(s)

1. Farzad Naeim
Vice President
, John A. Martin & Associates
Los Angeles CA 90015, USA
Email:farzad@johnmartin.com FAX: (213) 483-3084

[Save page as](#)

